

PRODUCTS TECHNICAL DATA

Product datasheet Issue No 3 Issued Oct 2015

RA 2027 High Performance Hot-Melt Rubber Resin Transfer tape (TOFFEE TAPE)

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Available Thicknesses		0.200 - 0.8mm	
Release liner thickness		0.130	mm
180 degree peel adhesion:	Open side	>1000	N/m
	Closed side	N/A	N/m
Polyester loop tack:	Open side	>1000	N/m
	Closed side	N/A	N/m
Liner release		90	gsm
Tensile strength		N/A	N/m
Elongation at break		4	%
Service temperature, continuous		-10 to +60	Deg. C.
UV Resistance		Moderate	
Recommended application temperature		+10 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		>10	Hours
Shelf life		12	Months

Test Methods: BS 7116

*provides good bonding of LSE materials

The values quoted above are based on limited test data and may be subject to change

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.