

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 7 Issued Jan 16

RA 2056 DOUBLE-SIDED HIGH TACK TISSUE TAPE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

| | | |
|-------------------------------------|--|---------|
| Adhesive Type | Pressure Sensitive Hot-Melt Rubber Resin | |
| Thickness, adhesive + carrier | 0.085 | mm |
| Release liner thickness | 0.055 | mm |
| 180 degree peel adhesion: | | |
| Open side | 1100 | N/m |
| Closed side | 1100 | N/m |
| Polyester loop tack: | | |
| Open side | 1000 | N/m |
| Closed side | 1000 | N/m |
| Liner release | 65 | gsm |
| Tensile strength | 1000 | N/m |
| Elongation at break | 4 | % |
| Service temperature | -40 to +60 | Deg. C. |
| Recommended application temperature | +5 to +25 | Deg. C. |
| Shear adhesion, 1Kg @ 23 deg. C. | > 50 | Hours |
| Shelf life | 12 | Months |

Test Methods: BS 7116

Standard fingerlift formats

6/12, 9/15, 12/18, 18/24, 24/30
Other formats, inc. offset fingerlift
available subject to min. quantities

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN
UK. Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526-5151 Fax: +44(0)121- 568-6797

