

2000 SERIES

TECHNICAL DATA



Product datasheet Issue No 8 Issued Mar 2021

RA 2057 DOUBLE-SIDED POLYPROPYLENE TAPE WHITE GLASSINE PAPER LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type :		Pressure Sensitive Hot Melt Rubber Resin	
Thickness, adhesive + carrier		0.080	mm
Release liner thickness		0.055	mm
180 degree peel adhesion:	Open side	1000	N/m
	Closed side	1000	N/m
Polyester loop tack:	Open side	1000	N/m
	Closed side	1000	N/m
Liner white glassine		65	gsm
Tensile strength		2200	N/m
Elongation at break		75	%
Service temperature		-10 to +60	Deg. C.
Recommended application temperature		+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		Greater than 100	Hours
Shelf life		12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797