

# 2000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Product datasheet Issue No. 8 Issued May 16

### RA 2065 DOUBLE-SIDED GENERAL PURPOSE FINGERLIFT TISSUE TAPE

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier

0.085

mm

Release liner thickness

0.055

mm

180 degree peel adhesion:

Open side

1000

N/m

Liner side

1000

N/m

Polyester loop tack:

Open side

1100

N/m

Liner side

1100

N/m

Liner release

65

gsm

Tensile strength

1100

N/m

Elongation at break

4

%

Service temperature

-10 to +60

Deg. C.

Recommended application temperature

+5 to +25

Deg. C.

Static shear adhesion, 1Kg @ 23 deg. C.

Greater than 100

Hours

Shelf life

12

Months

Standard product formats

6/12, 9/15, 12/18, 18/24, 24/30  
Other formats, inc. offset fingerlift  
available subject to min quantities

mm

FDA Approval

175.105

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.  
Email: sales@paladhesives.co.uk  
Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797