

2000 SERIES

TECHNICAL DATA



Product datasheet Issue No 5

Issued Jan 16

RA 2073 DOUBLE-SIDED TAPE GENERAL PURPOSE POLYPROPYLENE TAPE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier	0.090	mm
Release liner thickness	0.055	mm
180 degree peel adhesion:		
Open side	1000	N/m
Closed side	1000	N/m
Polyester loop tack:		
Open side	1100	N/m
Closed side	1100	N/m
Liner release	65	gsm
Tensile strength	2200	N/m
Elongation at break	75	%
Service temperature	-10 to +60	Deg. C.
Recommended application temperature	-5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	> 100	Hours
Shelf life	12	Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



**PAL ADHESIVE
PRODUCTS Ltd**

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN
UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121-568-6797