

2000 SERIES

TECHNICAL DATA



Product datasheet Issue No 1 Issued June 2010

RA 2304 PERMANENT REINFORCED TRANSFER TAPE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier	0.070	mm
Release liner type	White Glassine Liner	
Release liner thickness	0.055	mm
180 degree peel adhesion:		
Open side	1200	N/m
Closed side	1400	N/m
Polyester loop tack:		
Open side	1400	N/m
Closed side	1100	N/m
Liner release	65	gsm
Service temperature	-40 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shelf life	12	Months

Test Methods: BS 7116

The individual ingredients of the adhesive have been tested and approved for indirect food contact to the FDA specification 175.105

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



**PAL ADHESIVE
PRODUCTS Ltd**

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797