

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No. 1 Issued January 2014

RA 2811 DOUBLE-SIDED HIGH TACK FINGERLIFT TISSUE TAPE

BLACK "REMOVE TO EXPOSE" RELEASE LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier

0.085

mm

Release liner thickness

0.055

mm

180 degree peel adhesion:

Open side

1200

N/m

Liner side

1200

N/m

Polyester loop tack:

Open side

1350

N/m

Liner side

1350

N/m

Liner release

65

gsm

Tensile strength

1100

N/m

Elongation at break

4

%

Service temperature

-10 to +60

Deg. C.

Recommended application temperature

+5 to +25

Deg. C.

Static shear adhesion, 1Kg @ 23 deg. C.

Greater than 24

Hours

Shelf life

12

Months

Standard product formats

6/12, 9/15, 12/18, 18/24, 24/30
Other formats, inc. offset fingerlift
available subject to min quantities

mm

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797