

# 2000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Product datasheet Issue No 2 Issued April 16

### RA 2913 DOUBLE-SIDED POLYESTER FILM - BAG SEAL TAPE FILMIC RELEASE LINER

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Adhesive Type : Pressure Sensitive High Tack Hot Melt Grade

Thickness, adhesive + carrier	0.110	mm
Release liner thickness	0.050	mm

Film colours available	Clear,pink,blue	
------------------------	-----------------	--

180 degree peel adhesion:	Open side	1400	N/m
	Closed side	1400	N/m

Polyester loop tack:	Open side	1500	N/m
	Closed side	1500	N/m

Liner release	50 $\mu$ Film	
---------------	---------------	--

Tensile strength	4600	N/m
------------------	------	-----

Elongation at break	120	%
---------------------	-----	---

Service temperature	-10 T0 +60	Deg. C.
---------------------	------------	---------

Recommended application temperature	+5 to +25	Deg. C.
-------------------------------------	-----------	---------

Shear adhesion, 1Kg @ 23 deg. C.	>100	Hours
----------------------------------	------	-------

Shelf life	12	Months
------------	----	--------

Test Methods: BS 7116

The individual ingredients of the the adhesive have been tested and approved for indirect food contact to the FDA specification 175.105

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797