

3000 SERIES

TECHNICAL DATA



Product datasheet Issue No 4 Issued Nov 21

RA 3012 DOUBLE-SIDED TISSUE TAPE MODIFIED ACRYLIC ADHESIVE

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.080	mm
Release liner thickness	0.070	mm
180 degree peel adhesion: Open side	750	N/m
Closed side	750	N/m
Polyester loop tack: Open side	850	N/m
Closed side	850	N/m
Liner release	80	gsm
Tensile strength	1000	N/m
Elongation at break	4	%
Service temperature	-20 to +120	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	20	Hours
Shelf life	12	Months
Test Methods: BS 7116		
F&DA Approval	175.105	

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN
UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 505-1487