



Product datasheet Issue No 2

Issued June 2022

## RA 3221 PERM/PEEL FILMIC ACRYLIC DOUBLE-SIDED TAPE, WHITE PAPER LINER

TECHNICAL DETAILS		TYPICAL VALUE	<u>UNITS</u>
Adhesive System		Pure Emulsion Acrylic	
Thickness, adhesive + carrier Release liner thickness		0.050 0.055	mm mm
180 degree peel adhesion:	Open side Closed side	400 150	N/m N/m
Polyester loop tack:	Open side Closed side	800 100	N/m N/m
Liner		65	gsm
Tensile strength		4600	N/m
Elongation at break		12	%
Service temperature		-20 TO +120	Deg. C.
Recommended application temperature		+5 TO +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		>2	Hours
Shelf life		12	Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETEMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



Darlaston Rd industrial Estate, Darlaston Rd ,Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151 Fax: +44(0)121- 568 - 6797