

3000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 4

Issued Jan 21

RA 3222 PERM/PEEL FILMIC, HIGH-TACK OPEN SIDE DOUBLE-SIDED TAPE, WHITE PAPER LINER

<u>TECHNICAL DETAILS</u>		<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier		0.050	mm
Release liner thickness		0.055	mm
Adhesive types		Liner side Emulsion Acrylic, Open side hotmelt rubber resin	
180 degree peel adhesion:	Open side	1000	N/m
	Closed side	150	N/m
Polyester loop tack:	Open side	1000	N/m
	Closed side	100	N/m
Liner release		65	Gsm
Tensile strength		4600	N/m
Elongation at break		120	%
Service temperature		-20 TO +60	Deg. C.
Recommended application temperature		+5 TO +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		>2	Hours
Shelf life		12	Months
Test Methods: BS 7116			

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd Wednesbury, WS10 7TN
UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797