

3000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 1

Issued November 2013

RA 3226 PEEL / PEEL FILMIC

ACRYLIC DOUBLE-SIDED TAPE, WHITE LINER, (PEELABLE BOTH SIDES)

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Thickness, adhesive + carrier	0.060	mm
Release liner thickness	0.065	mm
180 degree peel adhesion: Open side	150	N/m
Closed side	150	N/m
Polyester loop tack: Open side	100	N/m
Closed side	100	N/m
Liner release	10	N/m
Tensile strength	4600	N/m
Elongation at break	12	%
Service temperature	-20 TO +120	Deg. C.
Recommended application temperature	+5 TO +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	>2	Hours
Shelf life	12	Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568-6797