

3000 SERIES

TECHNICAL DATA



Product datasheet Issue No 1 Issued July 2021

RA3515 DOUBLE-SIDED HIGH COAT WEIGHT TISSUE TAPE PURE EMULSION ACRYLIC ADHESIVE (AMBER RELEASE)

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Thickness, adhesive + carrier	0.115	mm
Release liner thickness	0.07	mm
180 degree peel adhesion: Open side	600	N/m
Closed side	600	N/m
Polyester loop tack: Open side	650	N/m
Closed side	650	N/m
Liner release	80	gsm
Tensile strength	2200	N/m
Elongation at break	75	%
Service temperature	-20 to +140	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	20	Hours
Shelf life	12	Months

Test Methods: BS 7116

The individual ingredients of the adhesive have been tested and approved for indirect food contact to the FDA specification 175.105

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd Wednesbury, WS10 7TN UK
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568-7152