

PRODUCTS TECHNICAL DATA

Issue No 1 Issued June 22

RAS 76155 FOAM ANTI HOTSPOT TAPE FOR POLYTHENE TUNNEL GREENHOUSES

****COLD WEATHER FORMULA****

| <u>TECHNICAL DETAILS</u> | <u>TYPICAL VALUE</u> | <u>UNITS</u> |
|-------------------------------------|----------------------|--------------|
| Thickness, adhesive only | 0.080 | mm |
| Standard Foam thicknesses | 3 | mm |
| 180 degree peel adhesion: | 600 | N/m |
| Polyester loop tack: | 800 | N/m |
| Liner release | 10 | N/m |
| Tensile strength | 1000 | N/m |
| Elongation at break | 4 | % |
| UV resistance | Excellent | |
| Service temperature | -40 to +140 | Deg. C. |
| Recommended application temperature | +5 to +25 | Deg. C. |
| Shear adhesion, 1Kg @ 23 deg. C. | 100 | Hours |
| Shelf life | 12 | Months |
| Test Methods | | BS 3924 |

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797