

PRODUCTS TECHNICAL DATA

Product datasheet Issue No 6

Issued Feb 19

RA 8070 DOUBLE-SIDED TISSUE TAPE SOLVENT ACRYLIC ADHESIVE

(PRODUCT ALSO AVAILABLE IN A.T.G FORMAT)

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.15	mm
Release liner thickness	0.10	mm
180 degree peel adhesion:		
Open side	900	N/m
Closed side	900	N/m
Polyester loop tack:		
Open side	1100	N/m
Closed side	1100	N/m
Liner	110	gsm
Tensile strength	1000	N/m
Elongation at break	4	%
Service temperature, continuous	-40 to +140	Deg. C.
Temperature exposure short term	200 < 1min	Deg. C
Plasticizer Resistance		Excellent
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	>80	Hours
Shelf life	12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.

