

PRODUCTS TECHNICAL DATA

Product data sheet Issue No. 1 Issued June 2020

RA8625F DOUBLE-SIDED POLYETHYLENE FOAM TAPE SOLVENT ACRYLIC ADHESIVE, 2.0mm THICK WHITE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Thickness, adhesive plus foam		2.08	mm
Release liner thickness		0.80	mm
Release liner type		Green PE film	
Foam type		Crosslinked Polyethylene	
Foam density		65	Kg/cu.m.
180 deg. Peel adhesion:	Open side	1600*	N/m
	Liner side	1600*	N/m
Polyester loop tack:	Open side	1200*	N/m
	Liner side	1200*	N/m
		*Mixture of peel/foam tear	
Shear adhesion, 1Kg 25mm sq.		10	hours
Liner release		10	N/m
Tensile strength,	M.D.	1215	kPa
	C.D.	775	kPa
Elongation at break	M.D.	225	%
	C.D.	275	%
Service temperature		-40 to +70 long term	Deg. C
		-40 to +90 short term	Deg. C
weather resistance		Excellent - suitable for outdoor use	
Recommended application temperature		+5 to +25	Deg. C
Shelf life		12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568-6797