

# PRODUCTS TECHNICAL DATA

Product data sheet Issue No. 1 Issued June 2011

## RA8625H DOUBLE-SIDED POLYETHYLENE FOAM TAPE ACRYLIC ADHESIVE, 2.0mm THICK BLACK

### TECHNICAL DETAILS

### TYPICAL VALUE

### UNITS

Thickness, adhesive plus foam		2.08	mm
Release liner thickness		0.80	mm
Release liner type		White PE Coated	
Foam type		Crosslinked Polyethylene	
Foam density		65	Kg/cu.m.
180 deg. Peel adhesion:	Open side	1600*	N/m
	Liner side	1600*	N/m
Polyester loop tack:	Open side	1200*	N/m
	Liner side	1200*	N/m
Shear adhesion, 1Kg 25mm sq.		*Mixture of peel/foam tear 10	hours
Liner release		10	N/m
Tensile strength,	M.D.	1215	kPa
	C.D.	775	kPa
Elongation at break	M.D.	225	%
	C.D.	275	%
Service temperature		-40 to +70 long term	Deg. C
		-40 to +90 short term	Deg. C
weather resistance		Excellent - suitable for outdoor use	
Recommended application temperature		+5 to +25	Deg. C
Shelf life		12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.  
Email: [sales@paladhesives.co.uk](mailto:sales@paladhesives.co.uk)  
Tel: +44 (0)121 - 526 5151 Fax: +44(0)121- 568-6797